High Brightness Seamless Indoor Full Color LED Display Screen P5 Led Video Wall

Basic Information

- Place of Origin:
- Brand Name:
- Vegoo CE/ROHS/FCC/

China

- Certification:
- Model Number:
- Minimum Order Quantity:
- Packaging Details:
- Delivery Time:
- Supply Ability:
- VG-FD 3 1 Sq.m
- Plywood case / Flight case / Carton box

3000 Sq.m / month

- 15 working days



Product Specification

- Product Name:
- Pixel Pitch:
- Pixel Configuration:
- Density:
- Moduel Size(L×W)mm:
- Contrast:
- Highlight:

- P5 Indoor Full Color LED Display
- 5mm
 - 1R1G1B/SMD2121 Black Lamp
 - 40,000 Pixel/m2
- 320mm×160mm
- 1000:1
- indoor advertising led display, indoor full color led display screen



Our Product Introduction

Product Description

Quick Detail:

Indoor Full Color LED Display Features:

- 1. Relatively low cost;
- 2. Stable capability;
- 3. Low energy consumption;
- 4. Good after-sale

Description:

P5 seamless indoor led screens

- 1) Relatively low cost
 2) Stable capability

- 3) High brightness4) Satisfactory after-sales

P5 Indoor Full color LED Display Specification:

Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2121 Black lamp
Density	40,000 pixel/m2
Moduel Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	640mm×640mm×90mm
Module Resolution	64×32
Cabinet Resolution	128×128
Driving Method	1/16 Scan
Driving IC	MBI5124
Brightness	600CD/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Bower Consumption	Max Power: 500W
Power Consumption	Average power: 200W
Module Weight	0.45kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
	Working : -20 - 65 °C
Operating Temperature	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7

Power Supply	AC 110-220V
Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



Services Before-sale:

Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone. Consider the demands of clients carefully, study the situation of the installation condition, Team up the related staff and workers promptly, give clients design program details to help them choose the products which they wanted as soon as possible

Service In - sales :

Try the best to meet the reasonable demands by clients Provisional changed .

Keep close touch with the clients during the period if installation .

Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

Service After-sale:

Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee.

You can down load and upgrade the related operating software of Led display freely from our company website , so as to resolve the problems when you use our led display .

Check the quality of appliance , do maintenance job and ask good suggestions form clients on a regular time schedule . Customer Service

1) Guarantee Time: Within one year after delivery form factory

2) Maintenance Coverage : LED modules, Power supply , Control system and other accessories (This warranty exclude accessories purchasing form other factory)

3) Maintenance Mode :

By returned maintenance , through express or by other way

4) Response time for maintenance :

Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user; Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours; On-site mode: (only for user inside china) after receiving maintenance request, we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions, problems could be solved on the basis of friendly negotiation between two parties.

Upgrade Service :

Unschedule, we will upgrade our system of products without extra formal; we'll do our best to help users with upgrading ; the following conditions are excluded by this warranty :

Without approved documents;

Series code on products having been torn or changed ;

Damage caused by lighting strike or electrical problems;

Risks caused by irresistible incidents includes all kinds of natural disasters, fire, wars, policy changes, and some other human error accidents.

Users or third party refit or repaired by themselves without VEGOO's permission ;

Water intrusion or corrosion caused by improper keeping or operating ; Over period of free maintenance .
Vegoo Shenzhen Weigu Electronic Technology Co., Ltd.
S 86-15118043086 S Linda@vegooled.com Aled-display.com
806 Building 1 Geya Technology Building, Clock Base, Ma Tou community,Ma Tian Street,Guangming District , Shenzhen,China