

## High Contrast Ratio Advertising P3 Indoor Full Color LED Display 111111pixel/M2

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



### Product Specification

- Product Name: P3 Indoor Full Color LED Display
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Density: 111,111pixel/m2
- Module Size(L×W)mm: 192mm×192mm
- Brightness: 800cd/
- Contrast: 1000:1
- Highlight: full color led display board,  
indoor full color led display screen



for more products please visit us on [hdled-display.com](http://hdled-display.com)

## Product Description

### High contrast ratio P3 Indoor Full color LED Display 111,111pixel/m2

#### Description:

1. High quality LED chip and high anti-static electricity capacity.
2. Large viewing angle and smooth displaying provide excellent visual effect from every angle.
3. high brightness, low attenuation, high reliability and weather ability.
4. High contrast ratio

#### P3 Indoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	3mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	111,111pixel/m2
4	Module Size(L×W)mm	192mm×192mm
5	Cabinet Size(L×W×H)mm	576mm×576mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	192×192
8	Driving Method	1/32 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	800cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 800W
14		Average power: 200W
15	Module Weight	0.25kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

#### Application Areas :

---- Sports halls, fields, playgrounds.

- Airports, bus stations and railway passenger terminals.
- Facades of shopping malls, department stores, banks and car dealerships.
- Architecture and social projects, information systems in cities.
- Show-business, concerts, festivals, motor shows and other public events.



**Products exchanged or returned :**

we supply our products strictly according to the contract list , if the quantity or specification doesn't meet our contract list, the buyer can give objections within 3 days after received the products , we'll exchanged after company confirmed.

**Casual damage situation:**

We can provide corresponding fittings without extra fee when improper operation or unexpected artificial damaged arise .

**Over Guarantee time :**

You only have to pay maintenance cost such as labor costs , spare parts costs and round-trip costs !

**Services Before-sale:**

Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone.

Consider the demands of clients carefully , study the situation of the installation condition , Team up the related staff and workers promptly , give clients design program details to help them choose the products which they wanted as soon as possible

**Service In - sales :**

Try the best to meet the reasonable demands by clients Provisional changed .  
Keep close touch with the clients during the period if installation .  
Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

**Service After-sale:**

Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee.

You can down load and upgrade the related operating software of Led display freely from our company website , so as to resolve the problems when you use our led display .

Check the quality of appliance , do maintenance job and ask good suggestions form clients on a regular time schedule .



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,  
Shenzhen, China