

# High Brightness Rental P4 Indoor Full Color LED Display Screen Die Casting Aluminum

## **Basic Information**

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
 Model Number: VG-FD 3
 Minimum Order Quantity: 1 Sq.m

• Packaging Details: Plywood case / Flight case / Carton box

Delivery Time: 15 working daysSupply Ability: 3000 Sq.m / month



# **Product Specification**

Product Name:
 P4 Indoor Full Color LED Display

Certification: CE/ROHS/FCC

• Pixel Pitch: 4mm

• Pixel Configuration: 1R1G1B/SMD2121 Black Lamp

Density: 62,500 Pixel/m2
Moduel Size(L×W)mm: 256mm×128mm

Brightness: 1000cd/Contrast: 1000:1

 Highlight: full color led display board, indoor full color led display screen



## **Product Description**

#### High Brightness Rental P4 Indoor Led Video Display Screen Die Casting Aluminum

## Description:

- 1. Budget friendly product, ideal for basic rental and fixed installations.
- 2. Extremely close view distances and wide view angles.
- 3. Silent operation, little heat generated
- 4. Standard panel design makes stocking, transportation, construction, spare parts and maintenance easy and simple.
- 5. Lightweight and seamless, precision extruded aluminum section structure.
- 6. Real white, brilliant colors, breathtaking grayscale.

### Protection

dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

#### P4 Indoor Full color LED Display Specification:

Pixel Configuration	1R1G1B/SMD2121 Black lamp
Density	62,500 pixel/m2
Moduel Size(L×W)mm	256mm×128mm
Cabinet Size(L×W×H)mm	512mm×512mm×90mm
Module Resolution	64×32
Cabinet Resolution	128×128
Driving Method	1/16 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	1000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 610W
Power Consumption	Average power: 240W
Module Weight	0.2kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration	With Eight Optional Gamma Calibration Curve
Curve	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
	WindowsNT,Windows2000,WindowsXP,Windows7
Operating System Platform	VVIIIdowsivi, vviiidowszooo, vviiidowszi , vviiidowsz

### Applications:

Shopping Malls Music Venues and Concerts Large Offices Theater and Arts TV Shows Car Shows



#### **Customer Service**

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage: LED modules, Power supply, Control system and other accessories (This warranty exclude accessories purchasing form other factory )
- 3) Maintenance Mode:
- By returned maintenance, through express or by other way
- 4) Response time for maintenance:

Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user; Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours; On-site mode: (only for user inside china) after receiving maintenance request, we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions, problems could be solved on the basis of friendly negotiation between two parties.



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com