



Seamless P7.62 Indoor Full Color LED Display , Remote Control Video Wall Led Display

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



Product Specification

- Product Name: P7.62 Indoor Full Color LED Display
- Certification: CE/ROHS/FCC
- Pixel Pitch: 7.62mm
- Moduel Size(L×W)mm: 244mm×244mm
- Brightness: 1200cd/
- Contrast: 1000:1
- Highlight: **full color led display board, indoor advertising led display**



for more products please visit us on hdled-display.com

Product Description

Seamless P7.62 Indoor LED Screen 1200cd/ 17,777 pixel/m2

Description:

Have you ever thought over about how to display your fashionable, cutting-edge, prevailed costume in your shop and catch your customers' eyeball effectively?

Show case LED Display are more prevailed in shopping mall currently, which makes your clothing more vivid, clever, respectable and move-enabled.

Indoor HD LED Screen Main features:

Seamless splice, good appearance.

Good color mixture, high uniformity, showing vivid HD images by brightness and color correction.

Through combined different drive IC with control system, which can meet the demands for refresh rate.

Asynchronous control card alliance with 3G network, which reach to wireless remote control.

Remote Control

Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

P7.62 Indoor Full color LED Display Specification:

NO:	Product Name	Specification
1	Pixel Pitch	7.62mm
2	Pixel Configuration	1R1G1B/SMD3528 White lamp
3	Density	17,777 pixel/m2
4	Module Size(L×W)mm	244mm×244mm
5	Cabinet Size(L×W×H)mm	732mm×732mm×90mm
6	Module Resolution	32×32
7	Cabinet Resolution	96×96
8	Driving Method	1/8 Scan
9	Driving IC	MBI5124
10	Brightness	1200cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 650W
14		Average power: 300W
15	Module Weight	0.45kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7

35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature prevention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Application Areas :

- Outdoor advertising, digital billboards, advertising in big companies
- Sports halls, fields, playgrounds.
- Airports, bus stations and railway passenger terminals.
- Facades of shopping malls, department stores, banks and car dealerships.
- Architecture and social projects, information systems in cities.
- Show-business, concerts, festivals, motor shows and other public events.



Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage : LED modules,Power supply ,Control system and other accessories (This warranty exclude accessories purchasing form other factory)
- 3) Maintenance Mode :
By returned maintenance , through express or by other way
- 4) Response time for maintenance :
 1. Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;
 2. Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;
 3. On-site mode: (only for user inside china) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions , problems could be solved on the basis of friendly negotiation between two parties.

Vegoo 威固电子 Shenzhen Weigu Electronic Technology Co., Ltd.

☎ 86-15118043086 ✉ Linda@vegooled.com 🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District , Shenzhen, China

