

P5 Duel Side Taxi LED Display Taxi Roof Signs Screen 6000cd/

Basic Information

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
Model Number: VG-SD P5
Minimum Order Quantity: 1 pcs

• Packaging Details: Plywood case / Flight case / Carton box

• Delivery Time: 10 days



Product Specification

Product Name:
P5 Outdoor Full Color Advertising Display

• Pixel Pitch: 5mn

Pixel Configuration: 1R1G1B/SMD2727
Moduel Size(L×W)mm: 320mm×160mm

Module Resolution: 64×32Driving Method: 1/8 Scan

• Driving IC: MBI5124 Or ICN 2038S

• Contrast: 1000:1

• Highlight: taxi top led display, taxi top digital signage

Product Description

P5 Taxi top car top sign / taxi roof signs with duel side

Description:

We are advertising LED display screen manufacturer and global wholesaler of large outdoor and indoor full color electronic LED matrix display screens, LED signs and LED screens used for mayor advertising campaigns; placed next to highways, or LED message and video displays for football stadiums, electronic arrival and departure airport displays signs, LED screen displays for schools or shops and malls to highlight products and services.

P5 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2727
Density	40,000 pixel/m2
Moduel Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	64×32
Cabinet Resolution	192×192
Driving Method	1/8 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	6000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
	Max Power: 750W
Power Consumption	Average power: 225W
Module Weight	0.28kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 85-264V
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Upgrade Service:

Unschedule, we will upgrade our system of products without extra formal; we'll do our best to help users with upgrading; the following conditions are excluded by this warranty: Without approved documents; Series code on products having been torn or changed :Damage caused by lighting strike or electrical problems;Risks caused by irresistible incidents includes all kinds of natural disasters, fire, wars, policy changes, and some other human error accidents. Users or third party refit or repaired by themselves without VEGOO's permission; Water intrusion or corrosion caused by improper keeping or operating; Over period of free maintenance.

Products exchanged or returned:

we supply our products strictly according to the contract list, if the quantity or specification doesn't meet our contract list, the buyer can give objections within 3 days after received the products, we'll exchanged after company confirmed.

Casual damage situation:

We can provide corresponding fittings without extra fee when improper operation or unexpected artificial damaged arise .

Over Guarantee time:

You only have to pay maintenance cost such as labor costs, spare parts costs and round-trip costs!









hdled-display.com