



High Brightness Waterproof Dustproof P5 Taxi LED Display For Promotional Advertising

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-SD P5
- Minimum Order Quantity: 1 pcs
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 10 days
- Payment Terms: T/T
- Supply Ability: 8000sqm per month



Product Specification

- Product Name: P5 Outdoor Full Color Advertising Display
- Pixel Pitch: 5mm
- Pixel Configuration: 1R1G1B/SMD2727
- Density: 40,000 Pixel/m²
- Moduel Size(L×W)mm: 320mm×160mm
- Driving IC: MBI5124 Or ICN 2038S
- Brightness: 6000cd/
- Contrast: 1000:1
- Highlight: **taxi top digital signage, taxi rooftop advertising signs**



for more products please visit us on hdled-display.com

Product Description

waterproof, dustproof P5 Taxi LED Display for promotional advertising

Description:

high brightness, high refresh rate, good resolution; low current, low power consumption, long lifespan of screen body

Location: taxi roof, for promotional advertising

Use moveable mounting bracket for easy installation and maintenance

Protection

waterproof, dustproof, high temperature prevention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Remote Control

Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

P5 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2727
Density	40,000 pixel/m ²
Module Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	64×32
Cabinet Resolution	192×192
Driving Method	1/8 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	6000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 750W
	Average power: 225W
Module Weight	0.28kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%

Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 85-264V

Advantages

- Large viewing angle Horizontal 140 degree, vertical 140 degree.
- Original and vivid display effect will be seen in this scope with color excursion free and image distortion free.
- 6000cd/m2 brightness can be installed in different environment. Energy-saving and Environmental friendly design.

Products exchanged or returned :

we supply our products strictly according to the contract list , if the quantity or specification doesn't meet our contract list, the buyer can give objections within 3 days after received the products , we'll exchanged after company confirmed.

Casual damage situation:

We can provide corresponding fittings without extra fee when improper operation or unexpected artificial damaged arise .

Over Guarantee time :

You only have to pay maintenance cost such as labor costs , spare parts costs and round-trip costs !

 **Shenzhen Weigu Electronic Technology Co., Ltd.**

 86-15118043086

 Linda@vegooled.com

 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China