

High Brightness P5 Taxi LED Display Led Taxi Sign MBI5124 / ICN 2038S

Basic Information

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
 Model Number: VG-SD P5
 Minimum Order Quantity: 1 pcs

Packaging Details: Plywood case / Flight case / Carton box

• Delivery Time: 10 days



Product Specification

Product Name:
 P5 Outdoor Full Color Advertising Display

• Pixel Pitch: 5mn

Pixel Configuration: 1R1G1B/SMD2727
 Density: 40,000 Pixel/m2
 Moduel Size(L×W)mm: 320mm×160mm

• Cabinet Size(L×W×H)mm: 960mm×960mm×130mm

Module Resolution: 64×32
Cabinet Resolution: 192×192

• Highlight: taxi top led display, taxi top digital signage



Product Description

High brightness P5 Taxi LED Display MBI5124 or ICN 2038S

Description:

- 1) High cost performance.
- 2) Good Consistency and High resolution.
- 3) High brightness and refresh rate.
- 4) Good after-sale services.
- 5) In the premise of guaranteeing quality, our company sales at low profit and warranty for 2 years.

Protection

waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Remote Control

Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

P5 Outdoor Full color LED Display Specification

Dua di sat Massa	0
Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2727
Density	40,000 pixel/m2
Moduel Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	64×32
Cabinet Resolution	192×192
Driving Method	1/8 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	6000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 750W
	Average power: 225W
Module Weight	0.28kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024
	16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C

Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 85-264V

Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage: LED modules, Power supply, Control system and other accessories (This warranty exclude accessories purchasing form other factory)
- 3) Maintenance Mode:
- By returned maintenance, through express or by other way
- 4) Response time for maintenance:
- 1. Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;
- 2. Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;
- 3. On-site mode: (only for user inside china) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions, problems could be solved on the basis of friendly negotiation between two parties.

Upgrade Service:

Unschedule, we will upgrade our system of products without extra formal; we'll do our best to help users with upgrading; the following conditions are excluded by this warranty:

- 1. Without approved documents:
- 2. Series code on products having been torn or changed;
- 3. Damage caused by lighting strike or electrical problems;
- 4. Risks caused by irresistible incidents includes all kinds of natural disasters, fire, wars, policy changes, and some other human error accidents.
- 5. Users or third party refit or repaired by themselves without VEGOO's permission;
- 6. Water intrusion or corrosion caused by improper keeping or operating;
- 7. Over period of free maintenance.





86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China