



High Refresh Rate P4 Stage Led Video Wall With 160° Wide Viewing Angle

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3.91
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



Product Specification

- Product Name: Stage LED Screens
- Pixel Pitch: 3.91mm
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Density: 65,536 Pixel/m²
- Module Size(L×W)mm: 250mm×250mm
- Module Resolution: 64×64
- Cabinet Resolution: 128×128
- Driving Method: 1/16 Scan
- Contrast: 1000:1
- Highlight: stage led display, stage background led screen



for more products please visit us on hdled-display.com

Product Description

High refresh rate Wide viewing angle Stage LED Screens 3.91mm

Description:

- 1) Wide viewing angle: The horizontal and vertical viewing angles are so wide that it is suitable for the environment of wide Horizontal.
- 2) High contrast ,High refresh rate and High brightness that the content on the display remains clearly visible under direct sunlight without any delay, smear phenomenon.
- 3) The brightness can be adjustable to meet the need of changing requirement of customer in environment.
- 4) Energy saving and environment protection, antistatic, dust-proof, good heat dissipation, cost-effective .

P3.91 Indoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	3.91mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	65,536 pixel/m ²
4	Module Size(L×W)mm	250mm×250mm
5	Cabinet Size(L×W×H)mm	500mm×500mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	128×128
8	Driving Method	1/16 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	1000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 600W
14		Average power: 200W
15	Module Weight	0.52kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	160°
18	Vertical Viewing Angle	120°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V

36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)
----	------------	---

Products exchanged or returned :

we supply our products strictly according to the contract list , if the quantity or specification doesn't meet our contract list, the buyer can give objections within 3 days after received the products , we'll exchanged after company confirmed.

Casual damage situation:

We can provide corresponding fittings without extra fee when improper operation or unexpected artificial damaged arise .

Over Guarantee time :

You only have to pay maintenance cost such as labor costs , spare parts costs and round-trip costs !



Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China