


Light Weight Railway Stations / Stage LED Screens P3.91mm 65536 Pixel/M2

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3.91
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



Product Specification

- Product Name: Stage LED Screens
- Pixel Pitch: 3.91mm
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Density: 65,536 Pixel/m2
- Moduel Size(L×W)mm: 250mm×250mm
- Cabinet Size(L×W×H)mm: 500mm×500mm×90mm
- Driving Method: 1/16 Scan
- Driving IC: MBI5124 Or ICN 2038S
- Highlight: stage led display, stage led video wall



Product Description

Description:

- 1) Super good pixels
- 2) super good refresh rate
- 3) Digital gray-scale technology
- 4) Energy-saving design cycle
- 5) Very good heat dissipation system
- 6) Light weight,can be customized color
- 7) Enclosure structure strong and durable

Our Product Introduction

Using Range :

Widely used in a variety of needs large hall, sports arena, banking, telecommunications , government agencies, terminal. pier, railway stations, the stock market and other trading market , medical systems, electric power, galleries and other publicity, advertising , information dissemination, the guise places

P3.91 Indoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	3.91mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	65,536 pixel/m2
4	Module Size(L×W)mm	250mm×250mm
5	Cabinet Size(L×W×H)mm	500mm×500mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	128×128
8	Driving Method	1/16 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	1000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 600W
14		Average power: 200W
15	Module Weight	0.52kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	160°
18	Vertical Viewing Angle	120°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V

Upgrade Service :

Unschedule,we will upgrade our system of products without extra formal; we'll do our best to help users with upgrading ; the following conditions are excluded by this warranty :

1. Without approved documents;
2. Series code on products having been torn or changed ;
3. Damage caused by lighting strike or electrical problems;
4. Risks caused by irresistible incidents includes all kinds of natural disasters, fire, wars, policy changes, and some other human error accidents.
5. Users or third party refit or repaired by themselves without VEGOO's permission ;
6. Water intrusion or corrosion caused by improper keeping or operating ;
7. Over period of free maintenance .

□

Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com

hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China