

1R1G1B/DIP 346 P10 Outdoor Full color LED Display 7500cd/

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD P10
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 3-5 days
- Supply Ability: 3000Sq.m



Product Specification

- Product Name: P10 Outdoor Full Color LED Display
- Pixel Pitch: 10mm
- Pixel Configuration: 1R1G1B/DIP 346
- Density: 10,000 Pixel/m²
- Cabinet Size(L×W×H)mm: 960mm×960mm×130mm
- Module Resolution: 32×16
- Cabinet Resolution: 96×96
- Driving Method: 1/ 4 Scan
- Contrast: 1000:1
- Highlight: outdoor digital signage displays,
outdoor full color led screen



Product Description

Description:

Stable Performance:

Internal connection within cabinet is simple, HUB card and modules use copper-plated pin directly connected. As we all know, the fewer components used in electronic products, the lower failure rate. Compared to traditional cable connection, I-Magic work more stable and reliable.

Extremely High Accuracy

Use of aluminum structure for the cabinets, one-time die-casting, creating exquisite work, the flatness of the entire screen when assembling is very high, and the gap between cabinets is less than 0.3mm, can't be detected by naked eyes, outstanding display effect.

P10 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	10mm
Pixel Configuration	1R1G1B/DIP 346
Density	10,000 pixel/m ²
Module Size(L×W)mm	320mm×160mm or 160mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	32×16
Cabinet Resolution	96×96
Driving Method	1/ 4 Scan
Driving IC	MBI5124
Brightness	7500cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Module Weight	0.5kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Control Distance	cable100m, Multimode500m, Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT, Windows2000, WindowsXP, Windows7
Power Supply	AC 110-220V
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Service and Guarantees

Services Before-sale: Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone. Consider the demands of clients carefully, study the situation of the installation condition, Team up the related staff

and workers promptly , give clients design program details to help them choose the products which they wanted as soon as possible

Service In - sales :Try the best to meet the reasonable demands by clients Provisional changed .Keep close touch with the clients during the period if installation .Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

Service After-sale:Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee.You can down load and upgrade the related operating software of Led display freely from our company website , so as to resolve the problems when you use our led display .Check the quality of appliance , do maintenance job and ask good suggestions form clients on a regular time schedule .



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China