

High Brightness Outdoor Full Color LED Display P6 Led Module 27777 Pixel/M2

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 6
- Minimum Order Quantity: 1 sq.m
- Packaging Details: Flight case
- Delivery Time: 10-15 days
- Supply Ability: 3000sq.m/month



Product Specification

- Product Name: P6 Outdoor Full Color LED Display
- Pixel Pitch: 6mm
- Pixel Configuration: 1R1G1B/SMD3535
- Density: 27,777 Pixel/m2
- Moduel Size(L×W)mm: 192mm×192mm
- Cabinet Size(L×W×H)mm: 576mm×576mm×90mm
- Brightness: 6500cd/
- Contrast: 1000:1
- Highlight: outdoor advertising led display screen, outdoor digital signage displays



Product Description

high Brightness P6 Outdoor Full color LED Display 27777 pixel/m2

Quick Details:

1. 6mm pixel rgb, hd, big density, very bright
2. on-site professional service.
3. hotline service, fast response.
4. 2 years' warranty for entire screen.
5. adequate spare parts supply.
6. technical support on upgrades and replacement.
7. regular maintenance service.

Function and Technology Character:

1. Multi-form file formats, such as VGA, Video, AVI, MOV, MPG, DAT, VOB and so on are comprehensive.
2. Super correcting technology for distortion.
3. Connected and controlled by PC via Lan and remote control.
4. Information source can be camera, video, VCD, DVD, LD, TV and so on.
5. Clear picture without flicker and distortion.
6. Brightness, contrast, saturation can be adjusted by itself and manual.
7. Show everything with your PC does synchronously.
8. Multi-form language editions, such as English, French, Germany, Greek, Russian and so on.
9. One interface for sound signal and two for video signal at least.

P6 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	6mm
Pixel Configuration	1R1G1B/SMD3535
Density	27,777 pixel/m2
Module Size(L×W)mm	192mm×192mm
Cabinet Size(L×W×H)mm	576mm×576mm×90mm
Module Resolution	32×32
Cabinet Resolution	96×96
Driving Method	1/8 Scan
Driving IC	MBI5124
Brightness	6500cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 545W
	Average power: 165W
Module Weight	0.244kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%

Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China