

Remote Control Outdoor Full Color LED Display 4mm Led Screen 9500K - 11500K

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD P4
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 3-5 days
- Supply Ability: 3000Sq.m



Product Specification

- Product Name: P4 Outdoor Full Color LED Display
- Pixel Pitch: 4mm
- Pixel Configuration: 1R1G1B/SMD1921
- Density: 62,500 Pixel/m²
- Moduel Size(L×W)mm: 256mm×128mm
- Driving IC: MBI5124
- Brightness: 5000cd/
- Contrast: 1000:1
- Highlight: outdoor digital signage displays, outdoor full color led screen



Product Description

P4 Outdoor Full color LED Display truck mounted led screen

Remote Control

Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

Application:

Suit for advertisement, stage, stadium, exhibition, TV-Show, mansion video wall, shopping mall, banks, schools, bus station, airport, gym, market, factories, monitoring centers, hospitals, bars etc.

1. Video display for advertisement
2. Dynamic display for logo, text, video
3. Live broadcast for news, sport, concert...
4. Stage background
5. Information display for time, schedule, text

P4 Outdoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	4mm
2	Pixel Configuration	1R1G1B/SMD1921
3	Density	62,500 pixel/m ²
4	Module Size(L×W)mm	256mm×128mm
5	Cabinet Size(L×W×H)mm	512mm×512mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	128×128
8	Driving Method	1/8 Scan
9	Driving IC	MB15124
10	Brightness	5000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 1100W
14		Average power: 760W
15	Module Weight	0.208kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25		With Eight Optional Gamma Calibration Curve
26	The Opposite Calibration Curve	Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V

36	Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)
----	------------	---

Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage : LED modules,Power supply ,Control system and other accessories (This warranty exclude accessories purchasing form other factory)
- 3) Maintenance Mode :
- By returned maintenance , through express or by other way
- 4) Response time for maintenance :

1. Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;

2. Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;

3. On-site mode: (only for user inside china) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions , problems could be solved on the basis of friendly negotiation between two parties.



Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086 ✉ Linda@vegooled.com 🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China