

20mm Transparent LED Display For Advertising Easy Installation Cabinets

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-SD P20
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 20-25 working days
- Supply Ability: 3000 Sq.m/ Month



Product Specification

- Product Name: Outdoor Full Color LED Display
- Pixel Pitch: 20mm
- Pixel Configuration: 1R1G1B/DIP 346
- Density: 2,500 Pixel/m²
- Module Size(L×W)mm: 960mm×17mm
- Cabinet Size(L×W×H)mm: 960mm×320mm×90mm
- Module Resolution: 48×0.85
- Driving Method: 1 Scan
- Driving IC: MBI5124
- Brightness: 5500CD/
- Application: Advertising Show
- Description: Transparent Led Display
- Highlight: **transparent led display,**
transparent led video wall

for more products please visit us on hdled-display.com

Product Description

High quality 20mm Transparent LED Display easy installation Cabinets

abouts:

1. Made with high resolution and high quality led lamps.
2. Super thin cabinets, less than 51mm thickness, and light weight,only with 6kgs per panel,it is portable and easy to move
- 3.With transparent glass cover for good vision and protection,can be used as a windon screen directly
4. Exquisite and tasteful appearance due to structural wire layout
5. High refresh rate up 1920Hz,and high brightness up to 5500nits,suit for indoor and outdoor use
6. Packed with wooden case or flight case, convenient to be collected and move

Applications:

Trade display windows,show case,advertising show wall maintained, pubic building space
Glass curtain wall gain a good space visual effect indoor, such as in chain store, shopping mall,exhibition center, airport, metro station, automobile 4S shop, jewelry store, bank etc. which brings strong visual impact and sense of hierarchy for LED transparent display.

P20 DIP 346 Outdoor Specification sheets

Product Name	Specification
Pixel Pitch	20mm
Pixel Configuration	1R1G1B/DIP 346
Density	2,500 pixel/m ²
Moduel Size(L×W)mm	960mm×17mm
Cabinet Size(L×W×H)mm	960mm×320mm×90mm
Module Resolution	48×0.85
Cabinet Resolution	48×16
Driving Method	1 Scan
Driving IC	MBI5124
Brightness	5500CD/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 600W
	Average power: 450W
Cabinet Weight	18kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
	Working : -20 - 65 °C

Operating Temperature	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V



For better quotations, include:

- A self introduction
- Special requests, if any



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China