

Waterproof Stage Rental LED Display 1R1G1B/SMD3535 Pixel 1000:1 Contrast

Basic Information

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
Model Number: VG-RD 6
Minimum Order Quantity: Negotiation
Price: Negotiable
Packaging Details: Flight case
Delivery Time: 10-15 days
Payment Terms: L/C, T/T

Supply Ability: 3000sq.m/month



Product Specification

Product Name: Rental LED Display

Feature: WaterproofDensity: 22,545 Pixel/m2

• Cabinet Size(L×W×H)mm: 640mm×640mm×90mm

Brightness: 5500cd/Application: Stage

• Highlight: stage rental led display, led video wall rental

Product Description

Waterproof Stage Rental LED Display 1R1G1B/SMD3535 Pixel 1000:1 Contrast

Rental LED Display Advantages

High brightness: the products adopt super-high brightness LED, so that you can see clearly from a long distance even in strong sunshine.

Good effect: the products adopt non-linear calibration technology to realize clearer images with stronger feeling of layers.

High reliability: using distributed scanning technology and module design technology that make higher reliability and stability.

Diversified display modes: the products support multiple display modes.

Easy operation: the products adopt popular video playing software to facilitate system operations.

Convenient installation and maintenance of display modules

Energy saving and environment protection, antistatic, dust-proof, good heat dissipation, cost-effective.

Large 140° viewing angle

Rental LED Display Specification

Product Name	Specification
	6.67mm
Pixel Configuration	1R1G1B/SMD3535
	22,545 pixel/m2
	320mm×160mm
Cabinet	020111111×100111111
Size(L×W×H)mm	640mm×640mm×90mm
<u> </u>	48×24
	96×96
Driving Method	1/6 Scan
	MBI5124
	11-1-1-1-1
3	5500cd/
Contrast	1000:1
	Auto and Manual
Power Consumption	Max Power: 800W
	Average power: 400W
	0.5kg
	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024
	16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite	With Eight Optional Gamma Calibration Curve
Calibration Curve	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment	
Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of
Remote Control	

Services Before-sale:

Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone.

Consider the demands of clients carefully, study the situation of the installation condition, Team up the related staff and workers promptly, give clients design program details to help them choose the products which they wanted as soon as possible

Service In - sales :

Try the best to meet the reasonable demands by clients Provisional changed .

Keep close touch with the clients during the period if installation .

Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

Service After-sale:

Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee.

You can down load and upgrade the related operating software of Led display freely from our company website, so as to resolve the problems when you use our led display.

Check the quality of appliance , do maintenance job and ask good suggestions form clients on a regular time schedule .

Vegoo Shenzhen Weigu Electronic Technology Co., Ltd.

86-15118043086

Linda@vegooled.com

hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community,Ma Tian Street,Guangming District , Shenzhen,China