

Lower Decay Outdoor Full Color LED Display With Large Viewing Angle 140°

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD P4-512-1
- Minimum Order Quantity: negotiation
- Price: negotiation
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 3-5 days
- Payment Terms: L/C, T/T
- Supply Ability: 3000Sq.m



Product Specification

- Product Name: Outdoor Full Color LED Display
- Feature: Lower Decay
- Pixel Configuration: 1R1G1B/SMD1921
- Viewing Angle: 140°
- Moduel Size(L×W)mm: 256mm×128mm
- Cabinet Size(L×W×H)mm: 512mm×512mm×90mm
- Brightness: 5000cd/
- Contrast: 1000:1
- Highlight: **outdoor digital signage displays,
outdoor full color led screen**

for more products please visit us on hdled-display.com

Product Description

Lower Decay Outdoor Full Color LED Display With Large Viewing Angle 140°

Outdoor Full Color LED Display Description:

1. Adopting high quality led lamps, higher brightness, lower decay, and larger viewing angle.
2. Taking integrated cabinet design, easy to install and maintenance
3. Fire-proof , anti-UV (ultraviolet), resistant to high temperature, acid salt spray;

Outdoor Full Color LED Display Specification

Product Name	Lower Decay Outdoor Full Color LED Display With Large Viewing Angle 140°
Pixel Pitch	4mm
Pixel Configuration	1R1G1B/SMD1921
Density	62,500 pixel/m ²
Module Size(L×W)mm	256mm×128mm
Cabinet Size(L×W×H)mm	512mm×512mm×90mm
Module Resolution	64×64
Cabinet Resolution	128×128
Driving Method	1/8 Scan
Driving IC	MBI5124
Brightness	5000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 1100W
	Average power: 760W
Module Weight	0.208kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7

Outdoor Full Color LED Display Details



Welcome to Led Display - Your Visual Supplier - Provide you the Best Led Display Products from China - An idea of potential of LED Lighting but also Led Display, it is all about perspective, an unlimited potential

Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China