



Indoor LED Display Cube Column P2.5 Module size 320mm*160mm Pixel Density 160000 Right Angle Cabinets

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: VEGOO
- Certification: CE ROHS FCC
- Model Number: VG-CM
- Minimum Order Quantity: 1 SQM
- Price: USD 100-800 per M2
- Packaging Details: 0.2025 CBM
- Delivery Time: 8-15 working day
- Payment Terms: T/T
- Supply Ability: 3000SQM/MONTH



Product Specification

- Cabinet: Aluminum Die Casting
- Horizontal Viewing Angle: 140
- Vertical Viewing Angle: 140
- Signal Processing Grey Processing Control Distance Frame Frequency Refresh Rate Contr: 10 Or 14 Bit
- Grey Processing: 1024x1024x1024 16834x16834x16834
- Control Distance: Cable100m Multimode500m Single Mode 2km
- Frame Frequency: 65Hz
- Refresh Rate: >3840Hz
- Control Mode: Synchronous/Asynchronous
- Tube Chip Color: Full Color
- Pixels: 2.5mm
- Usage: Indoor



More Images



for more products please visit us on hdled-display.com

Product Description

Cube HD LED Display P2.5 Module 320mm*160mm Pixel Density 160000




- Six-sided cube is completely seamless connected
- High pixel density, clear and sharp picture
- High contrast, high resolution
- Aluminum structure
- 360°Full perspective broadcast, cube display, highlight personality
- Customized products, support floor standing install, suspended install, embedded installation.
- flight case package, protection perfectly

Parameters

NO:	Product Name	Specification
1	Pixel Pitch	2.5mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	160,000 pixel/m ²
4	Module Size(L×W)mm	160mm×160mm
5	Cabinet Size(L×W×H)mm	480mm×480mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	192×192
8	Driving Method	1/32 Scan
9	Driving IC	MBI5124/ICN2153/FM6353
10	Brightness	600cd/
11	Contrast	6000 :1

12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 900W
14		Average power: 270W
15	Cabinet Weight	4.2kg
16	Color Temperature	2000K—9500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	16bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V/5V60Hz
36	Protection	IP 45

 **Shenzhen Weigu Electronic Technology Co., Ltd.**

 86-15118043086

 Linda@vegooled.com

 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China