




Pixel Pitch 1.25 Mm Indoor Full Color LED Display Die Casting Aluminium Cabinet 400 x 300 mm Light Weight

Our Product Introduction


Basic Information

- Place of Origin: CHINA
- Brand Name: VEGOO
- Certification: CE ROHS FCC
- Model Number: VG-P3
- Minimum Order Quantity: 1 SQM
- Price: USD500-900 per m2
- Packaging Details: 0.2025 CBM
- Delivery Time: 8-15 working day
- Payment Terms: T/T
- Supply Ability: 3000 sqm per month



Product Specification

- Tube Chip Color: Full Color
- Cabinet Size: 400 Mm X 300 Mm
- Usage: Indoor
- Screen Dimension: Customized
- Warranty: 3 Years
- Brightness: 800cd/sqm
- Refresh Rate: 1920Hz-3840Hz
- Life Span: 100000hours
- Scan Mode: 1/16scan
- Pixels: 1.25mm
- Highlight: **full color led display board, indoor advertising led display**



More Images



for more products please visit us on hdled-display.com

Product Description

P3 Indoor Full color LED Display Specification		
NO:	Product Name	Specification
1	Pixel Pitch	1.25mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	640000pixel/m ²
4	Module Size(L×W)mm	200mm×112.5mm
5	Cabinet Size(L×W×H)mm	600mm×337.5×50mm
6	Module Resolution	160×90
7	Cabinet Resolution	480×270
8	Driving Method	1/32 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	800cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 800W
14		Average power: 200W
15	Module Weight	0.25kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China