



High Resolution Indoor Full Color LED Display P3 Commercial Media Video Walls

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: VEGOO
- Certification: CE ROHS FCC
- Model Number: VG-P3-192
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: 0.2025 CBM
- Delivery Time: 8-15 working day
- Payment Terms: T/T
- Supply Ability: 3000 sqm per month



Product Specification

- Tube Chip Color: SMD Full Color
- Pixels: 3mm
- Cabinet Size: 576 X 576mm
- Usage: Indoor
- Screen Dimension: Customized
- Warranty: 3 Years
- Brightness: 800cd/sqm
- Refresh Rate: 1920Hz-3840Hz
- Application: Indoor
- Life Span: 100000hours
- Cabinet Material: Aluminum
- Highlight: indoor advertising led display,
indoor full color led display screen

for more products please visit us on hdled-display.com

Product Description

P3 Indoor Full color LED Display Specification

N O:	Product Name	Specification
1	Pixel Pitch	3mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	111000pixel/m2
4	Module Size(L×W)mm	192mm×192mm
5	Cabinet Size(L×W×H)mm	576mm×576
6	Module Resolution	
7	Cabinet Resolution	
8	Driving Method	
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	800cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 800W
14		Average power: 200W
15	Module Weight	0.25kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)