



P4.81 Rental Outdoor Full Color LED Display Event Cabinet 500 Or 1000mm

Our Product Introduction

Basic Information

- Place of Origin: Made in China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/CCC
- Model Number: VGrental
- Minimum Order Quantity: negotiation
- Price: negotiation
- Packaging Details: Flight case, 1mx1.2x1m
- Delivery Time: 15-25 days
- Payment Terms: T/T, Western Union
- Supply Ability: 5000sq.m/month



Product Specification

- Product Name: Moving Display
- Pixel Pitch: 4.81mm
- Pixel Configuration Indoor: 1R1G1B
- Module Size(L×W)mm: 250mm×250mm
- Cabinet Size 2: 500mm×500mm
- Cabinet Size(L×W×H)mm: 500mm×1000mm
- Brightness: 4500cd/
- Material: Nation Star LED
- Material1: Nova System
- Application: Rental Outdoor
- Type: Moving Display Rent Use Indoor And Outdoor
- Others: Curve
- Color: Full Color
- Highlight: **outdoor advertising led display screen,**

for more products please visit us on hdled-display.com

Product Description

P4.81 rental display outdoor event cabinet 500 or 1000mm

1:
Aluminum cabinet photos
500x500mm



Advantages:

Quick Assembly and Disassebmly

Adjustable Angle Lock, Flexible Stage Design

Slim and Light Weight Die Casting Aluminum Cabinet Design

Front Maintenance Magnetic Module

4K HD

Specification

Shenzhen WeiGu Electronic Technology Co.,Ltd.		
Outdoor Full color LED Display Specification		
N O:	Product Name	Specification
	1 Pixel Pitch	4.81mm
	2 Pixel Configuration	1R1G1B/SMD2727
	3 Density	43,243 pixel/m2
	4 Moduel Size(L×W)mm	250mm×250mm
	5 Cabinet Size(L×W×H)mm	500mm×500mm×90mm
6	Module Resolution	52×52

7	Cabinet Resolution	104×104
8	Driving Method	1/13 Scan
9	Driving IC	MBI5124
10	Brightness	4500cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 560W
14		Average power: 320W
15	Module Weight	0.663kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	140°
18	Vertical Viewing Angle	140°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Service and Guarantees

2 to 5 years guarantees

Technical support on site



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China