Flexible Ball LED Video Display Sphere Display Screen High Resolution Full Color Stage Backdrop

Basic Information

- Place of Origin:
- Brand Name: Vegoo
- Certification:
- Model Number:
- Minimum Order Quantity: Negotiable
- Price:
- Packaging Details:
- Delivery Time: 35-60 working days

China

CE/ROHS/FCC

VG-SUN8885

Negotiable

Plywood case / Flight case / Carton box



Product Specification

- Product Name:
- Pixel Pitch:
- Module Resolution:
- Cabinet Size(L×W×H)mm:
- Contrast:
- Color Temperature:
- Viewing Angle:Brightness:
- Highlight:

64×32
512mm×512mm×90mm
1000:1
9500K—11500K
360º
1000cd/

Ball LED Display

4mm

led ball screen, led display ball



More Images







Customed Flexible Ball LED Video Display Sphere Display Screen High Resolution Full Color Stage Backdrop

Vegoo Special LED panels Ball LED Display Screen

Customed SMD Flexible Ball LED Display Sphere Display Screen High Resolution Full Color Stage Backdrop Curved Advertising Led Display High Definition Video Ball in the Museum

Our core advantage:

- 1. wide viewing angle 360 degree
- 2. hi-uniformity screen, good view experience
- 3. Online single detect function, minitoring your product's status
- 4. Low power consumption, energy saving 35%
- 5. Ultra-thin, light module

Specification:

Product Name	P4 Indoor Full color LED Display
Pixel Pitch	4mm
Pixel Configuration	1R1G1B/SMD2121 Black lamp
Density	62,500 pixel/m2
Moduel Size(L×W)mm	256mm×128mm
Cabinet Size(L×W×H)mm	512mm×512mm×90mm
Module Resolution	64×32
Cabinet Resolution	128×128
Driving Method	1/16 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	1000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Dawar Canaumatian	Max Power: 610W
Power Consumption	Average power: 240W
Module Weight	0.2kg
Color Temperature	9500K—11500K
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110–220V
Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Applications:

advertising media, sports stadiums, dance floor, airport station integrated information dissemination, business establishments and public area etc.



Service and Guarantees

Services Before-sale:

Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone. Consider the demands of clients carefully, study the situation of the installation condition, Team up the related staff and workers promptly, give clients design program details to help them choose the products which they wanted as soon as possible

Service In - sales :

Try the best to meet the reasonable demands by clients Provisional changed . Keep close touch with the clients during the period if installation .

Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

Service After-sale:

Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee.

You can down load and upgrade the related operating software of Led display freely from our company website , so as to resolve the problems when you use our led display .

Check the quality of appliance , do maintenance job and ask good suggestions form clients on a regular time schedule

