

P4.81-P10 Outdoor Full Color LED Display / Video Wall Screens Waterproof Ip65

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: CHINA
- Brand Name: VEGOO
- Certification: CE ROHS FCC
- Model Number: VG-SUN8889
- Minimum Order Quantity: Negotiable
- Price: negotiable
- Packaging Details: poly wooden box, flight case , carton
- Delivery Time: 20working days
- Payment Terms: T/T
- Supply Ability: 8000 sqm/month




Product Specification

- Application: Outdoor
- Color: Full Color
- Warranty: 3years
- Material: Aluminum Or Iron
- LED Lamp: Nationalstar
- Control System: Nova
- Highlight: outdoor digital signage displays,
outdoor full color led screen



More Images



Product Description

High Brightness P4.81-P10 Outdoor LED Display Full Color Video Wall Screens Waterproof Ip65

Our advantages:

1. Supply custom service, you can have the best product as your thought.
2. Good quality: High brightness, High definition, High refresh rate, High gray level, Good color uniformity, full color, the perfect view feast.
3. After-sales service: you will get the quickly reply and resolution once you have any question.

Pixel Pitch	6mm
Pixel Configuration	1R1G1B/SMD3535
Density	27,777 pixel/m ²
Module Size(L×W)mm	192mm×192mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	32×32
Cabinet Resolution	160×160
Driving Method	1/8 Scan
Driving IC	FM6124
Brightness	6500cd/
Contrast	6000 :1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 810W
	Average power: 405W
Cabinet Weight	25kg
Color Temperature	2000K—9500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	16bit
Grey Processing	1024×1024×1024
	16834×16834×16834
Control Distance	cable100m, Multimode500m, Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT, Windows2000, WindowsXP, Windows7
Power Supply	AC 110-220V/5V60Hz
Protection	waterproof, dustproof, high temperature prevention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



FAQ

1. How long could i receive the inquiry reply ?

A: You will get a reply within 12 hours.

2.How should I place an order for led display?

Just contact us and show your needs,we will do specific plan for you and start production after deposit.

3.When will I received the goods ?

Normally 10-20days after deposit,some customed product need 30days more.

4.How about the after-sales service ?

We have a professional team which is charged 24-hour online service dealing with

your feedback to help you solving problems.



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China