

Lightweight Slim P5 SMD2727 Outdoor Full Color LED Display

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/CCC
- Model Number: VG-SUN88839
- Minimum Order Quantity: 1 unit
- Price: negotiation
- Packaging Details: Plywood case / Flight case / Carton
- Delivery Time: 5-25 days
- Payment Terms: L/C, T/T
- Supply Ability: 3000Sq.m



Product Specification

- Product Name: Outdoor LED Video Screen
- Pixel Pitch: 5mm
- Moduel Size(L×W)mm: 320×160
- Cabinet Size(L×W×H)mm: 640×640×130
- Contrast: 6000:1
- Brightness: 6000cd/
- Highlight: **SMD2727 smd led screen,
P5 outdoor led screen rental**



Product Description

High quality factory price P5 Outdoor advertising led display video screen

Our core advantage:

- 1, Slim and lightweight, clear display
- 2, Ultra high protection class
- 3, Flexible assembly

P5 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2727
Density	40,000 pixel/m ²
Module Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	640mm×640mm×130mm
Module Resolution	64×32
Cabinet Resolution	192×192
Driving Method	1/8 Scan
Driving IC	FM6124
Brightness	6000cd/
Contrast	6000 :1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 650W
	Average power: 325W
Cabinet Weight	12kg
Color Temperature	2000K—9500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	16bit
Grey Processing	1024×1024×1024
	16834×16834×16834
Control Distance	cable100m, Multimode500m, Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT, Windows2000, WindowsXP, Windows7
Power Supply	AC 110-220V/5V60Hz
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



Customer Service:

- 1) Warrenty: three year
- 2) Maintenance parts : LED modules,Power supply ,Control system and other accessories
- 3) Maintenance way :Returned to our factory through express or other way
- 4) Response time for maintenance :within 24hours

Vegoo 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China