

1R1G1B P6 6500cd/ Outdoor Full Color LED Display

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: CHINA
- Brand Name: VEGOO
- Certification: CE ROHS FCC
- Model Number: VG-SUN88841
- Minimum Order Quantity: 1 SQM
- Price: negotiate
- Packaging Details: flight case,plywood case,carton
- Delivery Time: 15-30 working days
- Payment Terms: T/T
- Supply Ability: 3000SQM/MONTH



Product Specification

- Product Name: P6 Outdoor Video Screen
- Driving Method: 1/8 Scan
- Pixels Density: 27,777 Pixel/m2
- Brightness: 6500cd/
- Cabinet Size: 576mm×576mm×90mm
- Control Mode: Synchronous/Asynchronous
- Highlight: **1R1G1B led signs outdoor, P6 outdoor led advertising, 6500cd/ outdoor led video display**



Product Description

Good quality factory directly P6 Outdoor led advertise video screen waterproof

- 1,high gray,large angle,ensure quality and delicate,high refresh rate to ensure video and photos without a moire phenomenon.
- 2,special structure and material design.
- 3,low consumption,long use life

P6 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	6mm
Pixel Configuration	1R1G1B/SMD3535
Density	27,777 pixel/m ²
Module Size(L×W)mm	192mm×192mm
Cabinet Size(L×W×H)mm	576mm×576mm×90mm
Module Resolution	32×32
Cabinet Resolution	96×96
Driving Method	1/8 Scan
Driving IC	FM6124
Brightness	6500cd/
Contrast	6000 :1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 810W
	Average power: 405W
Cabinet Weight	8.5kg
Color Temperature	2000K—9500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	16bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 °C
	Storage : -40 - 85 °C
Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V/5V60Hz
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



FAQ

Q1: What's the control system do you use?

A: Our control system is Novastar normally. Also support other controlling system.

Q2: Do you have any certification for LED display?

A: Yes, we have CE,ROHS,CCC certification.

Q3: How about the guarantee of led display?

A: We guarantee all our displays, modules, spare parts for three years.
During this time, we will replace it for free if there is something wrong with them.



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China